

International Epoxies & Sealers Material Safety Data Sheet

MSDS No: 1702 Super Cleaning Solvent (5 Gallon Pail)

Version No: 102009

Order No:

International Epoxies & Sealers, 30241 Commerce Dr.,
San Antonio FL 33576
1-800-451-7206

Emergency Assistance

For emergency assistance involving chemicals call
Infotrac at 1-800-535-5053
Outside the U.S.A, Call Collect: 1-352-323-3500

COMPANY IDENTITY: International Epoxies and Sealers
PRODUCT IDENTITY: Super Cleaning Solvent (5 Gallon Pail)
NEW MSDS DATE: 10/20/2009

DATE: 10/20/09
PAGE 1 OF 7

MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1, using the International Chemical Safety Cards of the Global Harmonizing System.

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this MSDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

PRODUCT IDENTITY: 1702 Super Cleaning Solvent (5 Gallon Pail)
MSDS NUMBER: 1702
MSDS DATE: 10/20/2009
COMPANY IDENTITY: International Epoxies and Sealers
COMPANY ADDRESS: 30241 Commerce Drive
COMPANY CITY: San Antonio FL 33576
COMPANY PHONE: 1-800-451-7206
INFOTRAC PHONE: 1-800-535-5053

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CONTAINS:

55-65% MEDIUM ALIPHATIC SOLVENT NAPHTHA (*64742-88-7),
25-35% ACETONE (67-64-1)[200-662-2],
0-10% TOLUENE (108-88-3)[203-625-9]

Number in parentheses is CAS #, number in brackets is European EC #.

This product has a mixture of n- and iso- paraffins, aromatic hydrocarbons, & naphthenes. Depending on the raw material & production processes, the composition & physical properties of this solvent can vary considerably. The contents of benzene is much less than 0.1% by volume.

SECTION 3. HAZARDS IDENTIFICATION

EXPOSURE PREVENTION: STRICT HYGIENE!

AVOID EXPOSURE OF (PREGNANT) WOMEN!

RISK STATEMENTS:

R36/37/38 Irritating to eyes, respiratory system and skin.
R48 Harmful: danger of serious damage to health by prolonged exposure.
R20/65 Harmful by inhalation, may cause lung damage if swallowed.
R12/13 Extremely Flammable! Serious static electricity fire hazard!
R63 Possible risk of harm to the unborn child.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapors may cause drowsiness and dizziness.

SAFETY STATEMENTS:

S36/37 Wear suitable protective clothing and gloves.
S2 Keep out of the reach of children.
S9 Keep container in a well-ventilated place.
S16 Keep away from sources of ignition. No smoking.
S23 Do not breathe gas, fumes, vapor, or spray.
S24 Avoid contact with skin.
S46 If swallowed, seek medical advice immediately, and show this container or label.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

International Epoxies and Sealers

ISSUE DATE:2009-10-20

Annotation:

COMPANY IDENTITY: International Epoxies and Sealers
PRODUCT IDENTITY: Super Cleaning Solvent (5 Gallon Pail)
NEW MSDS DATE: 10/20/2009

DATE: 10/20/09
PAGE 2 OF 7

SECTION 4. FIRST AID MEASURES

EYE CONTACT:

For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT:

In case of contact with skin immediately remove contaminated clothing.
Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SWALLOWING:

Rinse mouth. Do NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY.
Do NOT give liquids to an unconscious or convulsing person.

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES

NO open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

EXTINGUISHING MEDIA

Use dry powder, AFFF, foam, carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE

Keep container tightly closed.
Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Closed containers may explode if exposed to extreme heat.
Applying to hot surfaces requires special precautions.
Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE MEASURES:

EVACUATE DANGER AREA! Consult an expert!
Vapors may ignite explosively & spread long distances. Prevent vapor buildup.
Keep unprotected personnel away. Ventilate spill area. Remove all ignition sources.
Use self-contained breathing apparatus.

CONTAINMENT AND CLEAN-UP MEASURES:

Stop spill at source. Dike and contain. Collect leaking liquid in sealable containers.
Absorb remaining liquid in sand or inert absorbent. Remove to safe place.
Do NOT wash away into sewer. Do NOT let this chemical enter the environment.

COMPANY IDENTITY: International Epoxies and Sealers
PRODUCT IDENTITY: Super Cleaning Solvent (5 Gallon Pail)
NEW MSDS DATE: 10/20/2009

DATE: 10/20/09
PAGE 3 OF 7

SECTION 7. HANDLING AND STORAGE

HANDLING

Isolate from oxidizers, heat, sparks, electric equipment & open flame.
Use only with adequate ventilation. Avoid breathing of vapor or spray mist.
Avoid contact with skin & eyes.
Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.
Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.
Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

STORAGE

Vapors may ignite explosively & spread long distances. Prevent vapor buildup.
Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.
Keep in fireproof surroundings. Keep separated from strong oxidants.
Do not store above 49 C/120 F. Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION

LOCAL EXHAUST	: Necessary
MECHANICAL (GENERAL)	: Acceptable
SPECIAL	: None
OTHER	: None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.
Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers.
Wash at end of each workshift & before eating, smoking or using the toilet.
Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

International Epoxies and Sealers

ISSUE DATE:2009-10-20

Annotation:

COMPANY IDENTITY: International Epoxies and Sealers
PRODUCT IDENTITY: Super Cleaning Solvent (5 Gallon Pail)
NEW MSDS DATE: 10/20/2009

DATE: 10/20/09
PAGE 4 OF 7

SECTION 9. PHYSICAL DATA

APPEARANCE : Liquid, Water-White
ODOR : Ketone
BOILING RANGE : 67 134 198 C / 153 274 390 F
AUTO IGNITION TEMPERATURE : 276 C / 530 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol): 1.5
FLASH POINT (TEST METHOD): -16 C / 2 F (TCC) (Lowest Component)
FLAMMABILITY CLASSIFICATION: Class I B
GRAVITY @ 68/68 F / 20/20 C :
API : 48.3
SPECIFIC GRAVITY (Water=1) : 0.764
POUNDS/GALLON : 6.36
VOC'S (>0.44 Lbs/Sq In) : 38.0 Vol. % / 299.0 g/L / 2.490 Lbs/Gal
TOTAL VOC'S (TVOC) : 100.0 Vol. % / 786.9 g/L / 6.555 Lbs/Gal
NONEXEMPT VOC'S (CVOC) : 70.0 Vol. % / 550.9 g/L / 4.588 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS) : 8.0 Wt. % / 63.0 g/L / 0.524 Lbs/Gal
VAPOR PRESSURE (mm of Hg)@20 C 95.1
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) 2.3
VAPOR DENSITY (air=1) : 3.3
WATER ABSORPTION : Appreciable
REFRACTIVE INDEX : 1.414
MIXED ANILINE POINT (Acid Insol): 61 C / 142 F

SECTION 10. STABILITY & REACTIVITY

STABILITY

Stable under normal conditions.

CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID

Reacts violently with strong oxidants, causing fire & explosion hazard.
Attacks many plastics, coatings.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS #	TWA (OSHA)	TLV (ACGIH)	HAP
Medium Aliphatic Solvent Naphtha	*64742-88-7	500 ppm	100 ppm	No
Acetone	67-64-1	1000 ppm	500 ppm A4	No
Toluene	108-88-3	200 ppm	50 ppm A4	Yes

In addition to EPA Hazardous Air Pollutants showing `Yes' under "HAP" above, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%):
Benzene, Mixed Xylenes, Ethylbenzene

International Epoxies and Sealers

ISSUE DATE:2009-10-20

Annotation:

COMPANY IDENTITY: International Epoxies and Sealers
PRODUCT IDENTITY: Super Cleaning Solvent (5 Gallon Pail)
NEW MSDS DATE: 10/20/2009

DATE: 10/20/09
PAGE 5 OF 7

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

MATERIAL	CAS #	CEILING	STEL(OSHA/ACGIH)
Acetone	67-64-1	None Known	750 ppm

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.
Absorption thru skin increases exposure.
Primary irritation to eyes, redness, tearing, blurred vision.
Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Acute overexposure can cause harm to kidneys, blood, nerves, liver, lungs. Use of alcoholic beverages enhances the harmful effect.

SWALLOWING:

Harmful or fatal if swallowed.
Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.
The symptoms of chemical pneumonitis may not show up for a few days.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Chronic overexposure can cause harm to kidneys, blood, nerves, liver, lungs. Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Pregnant women should avoid use. May cause birth defects.
Leukemia been reported in humans from Benzene.
This product contains less than 24 ppm of Benzene.
Not considered hazardous in such low concentrations.
Absorption thru skin may be harmful.
Depending on degree of exposure, periodic medical examination is indicated.

International Epoxies & Sealers Material Safety Data Sheet

For Additional Information contact Customer Service during business hours, Eastern time: (800) 451-7206

Notice

IES expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, IES makes no representations as to its accuracy or sufficiency. Conditions of use are beyond IES's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process