

---

**1. CHEMICAL PRODUCT AND COMPANY INFORMATION**Product Name: **STIK-UMM WEATHERSTRIP ADHESIVE**Product Code(s): **225 / 226**

Manufacturer/Supplier: INTERNATIONAL EPOXIES &amp; SEALERS

30241 COMMERCE DRIVE

SAN ANTONIO, FL, USA

24 Hour Emergency Phone(s): 800-535-5053 (INFOTRAC)

OUTSIDE USA CALL COLLECT: 1-352-323-3500

Product Use: Adhesive

MSDS Prepared By: IES MSDS DEPT.

---

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredient(s) CAS Number % by Weight

\* Methylbenzene; Toluene 108-88-3 25- 40%

\* Hexane 110-54-3 15- 25%

Styrene-Butadiene Copolymer 9003-55-8 15- 25%

See Section 15. Regulatory Information for code descriptions

Weight percent (%) of 0.0 means chemical is in trace amounts.

---

**3. HAZARDS IDENTIFICATION**

DANGER! FLAMMABLE. IRRITANT.

HMIS Hazard Ratings: Health =2\*, Flammability =3, Chemical Reactivity =0

Note: HMIS ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

Potential Health Effects Eyes: Moderate irritation to the eyes. Exposure can cause redness and itching. Skin: Moderate irritation to the skin. May be absorbed through the skin causing liver, kidney or central nervous system damage. Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. Inhalation: Moderate irritation to the respiratory system. May be harmful if inhaled. High concentrations may be fatal. Ingestion: Moderate irritation to the digestive tract. May cause nausea.

---

**4. FIRST AID MEASURES**

Seek professional medical attention for all over-exposures and/or persistent problems.

Eyes Contact: Flush eyes with clean water for a minimum of 15 minutes. Seek medical attention.

Skin Contact: Wash exposed area thoroughly with soap and water.

Inhalation: Remove person from area to fresh air. If breathing difficulty persists, seek medical attention.

Ingestion: DO NOT INDUCE VOMITTING. Seek immediate medical attention.

---

**5. FIRE FIGHTING MEASURES**

Flammable Properties

Flash Point: -7 Deg F, -22 Deg C Method: TCC

Upper Explosive Limit (UEL): 7.5

Lower Explosive Limit (LEL): 1.1

Auto ignition Temperature: No data

Extinguishing Media: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog, Other.

Special Firefighting Procedures: Full fire fighter equipment including

SCBA should be worn to avoid skin contact and inhalation of concentrated vapors. Minimize skin exposure. Highly toxic fumes may be generated by thermal decomposition.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat or burst when contaminated with water (CO2 gas evolved). Hazards apply to empty containers. Combustion generates toxic fumes.

---

## 6. ACCIDENTAL RELEASE MEASURES

For large spills or transportation accidents involving release of this product, contact INFOTRAC at 800-535-5053.

Eliminate all sources of ignition, provide adequate ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Sweep up and dispose of in appropriate containers in accordance with Federal, State and/or Local regulations.

---

## 7. HANDLING AND STORAGE

Use non-sparking tools when handling this material. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Store in a cool area away from heat and flames. Do not reuse container when empty.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name/Exposure Limits CAS Number

---

\* Methylbenzene; Toluene 108-88-3

OSHA PEL: 200 ppm, 300 ppm ceiling

ACGIH TLV: 50 ppm (skin)

IDLH: 500 ppm

\* Hexane 110-54-3

OSHA PEL: 500 ppm, ACGIH TLV: 50 ppm, skin

IDLH 1100 ppm (10% LEL)

Styrene-Butadiene Copolymer 9003-55-8

OSHA PEL: NA, ACGIH TLV: NA, OTHER: NA

Engineering Controls: General mechanical ventilation or local exhaust should be utilized to keep vapor concentrations below exposure limits (PEL & TLV). Ventilation equipment must be explosion proof. Respiratory Protection: Utilize engineering controls to reduce emission levels below the time weighted exposure limits (ACGIH TLV & OSHA PEL). Wear an approved respirator if exposure limits are above the exposure limits listed above.

Eye Protection: Use safety glasses or splash goggles.

Skin Protection: Use chemical resistant gloves.

Safe Work Practices: Eye washes and safety showers in the workplace are recommended. Avoid contact with skin and eyes. Avoid breathing vapors. Wash hands thoroughly after using and before eating, drinking or smoking. Employee education and training in the safe use and handling of this product is required under the OSHA Hazard

Communication Standard 29CFR1200. Smoking in area where this material is used should be strictly prohibited. Always use protective clothing and equipment. Remove all contaminated clothing and wash thoroughly when finished working. Keep food and drink away from material and from area where material is being used.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Homogeneous mixture

Physical State: Viscous liquid

Color: Cloudy, colorless

Odor: Organic solvent

Odor Threshold: No Data

Specific Gravity (water=1) 0.87

Vapor Pressure: No data

Vapor Density: Heavier than air

Material VOC: 3.58 lb/gal 429 g/l

Coating VOC: 3.58 lb/gal 429 g/l

Evaporation Rate: Slower than Butyl Acetate

Boiling Point: 156 Deg F

Melting Point: No data

Freezing Point: No data

Viscosity at Ambient Temperature: No data

Solubility in Water: Insoluble

Octanol/Water Partition Coefficient: No data

pH: No data

---

**10. STABILITY AND REACTIVITY**

Stability: Stable

Incompatibility: Strong acids, strong bases and strong oxidizing agents.

Hazardous Polymerization: Will not occur.

---

**11. TOXICOLOGICAL INFORMATION**

Effects of Exposure:

ACUTE:

INHALATION - Dizziness, breathing difficulty, headaches, & loss of coordination.

EYE CONTACT - Moderate irritation, tearing, redness, and blurred vision.

SKIN CONTACT - Moderate irritant. Can dry and defat skin causing cracks, irritation, and dermatitis.

INGESTION - Can cause gastrointestinal irritation, vomiting, nausea, & diarrhea.

CHRONIC:

May affect liver, kidney and central nervous system with repeated exposure.

Acute Toxicity Data: No data.

Carcinogenicity: NTP -No, IARC -No, OSHA -No

This product has not been tested for carcinogenic effects. Some chemicals in this product may be identified by NTP, IARC and/or OSHA as carcinogenic, indicated above as "Yes". No further information available.

Teratology: No data.

Reproduction: No data.

Mutagenicity: No data.

---

**12. ECOLOGICAL INFORMATION**

No data.

---

**13. DISPOSAL CONSIDERATIONS**

Subject to hazardous waste generation, treatment, storage and disposal. Product should be disposed of in accordance with all governmental regulations. Subject to hazardous waste generation, treatment, storage and disposal under RCRA, 40CFR261. Product should be disposed of in accordance with all Federal, State and local regulations.

---

**14. TRANSPORT INFORMATION**

The following transportation information is provided based on INTERNATIONAL EPOXIES AND SEALERS interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking and labeling prior to offering for transport.

USA (DOT) Status: Consumer Commodity ORM-D For inner packaging not exceeding 5 L each packaged in a strong outer box:

CONSUMER COMMODITY ORM-D

Water (IMDG) Status: UN1133, Adhesive, 3, PGII

Air (ICAO,IATA) Status: UN1133, Adhesive, 3, PGII

Canada (TDG) Status: Consumer Commodity ORM-D For inner packaging not exceeding 5 L each packaged in a strong outer box:

CONSUMER COMMODITY

---

**15. REGULATORY INFORMATION**

The information listed in this section is not all inclusive of all regulations for this product or the chemical components of this product.

US Federal Regulations

TSCA Status: All known major components of this product are listed on the TSCA Inventory and/or are otherwise in compliance with TSCA.

SARA 302 (EHS) Status: No EHS chemicals present.

SARA 311/312 Status: Immediate Health Hazard, Delayed Health Hazard,

Fire Hazard.

SARA 313 Status: \* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

OSHA Status: This material meets the requirement of hazardous material and is subject to 29CFR1910.1200.

---

USA State Information

California Proposition 65: WARNING: This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm.

Pennsylvania RTK Status: This material contains chemical(s) subject to notification under Pennsylvania Right to Know.

New Jersey RTK Status: This material contains chemical(s) subject to notification under New Jersey Right to Know.

Massachusetts RTK Status: This material contains chemical(s) subject to notification under Massachusetts Right to Know.

Rhode Island RTK Status: This material contains chemical(s) subject to notification under Rhode Island Right to Know.

**International Regulations**

Canada

DSL Status: All known major components of this product are listed on the DSL Inventory and/or are otherwise in compliance with the DSL

NDSL Status: Contains no chemicals on the NDSL

WHMIS: B2D2B

New Zealand

HSNO Number: HSR002662

EINECS Status: All components of this material are listed on the EINECS Inventory.

---

**16. OTHER INFORMATION**

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by INTERNATIONAL EPOXIES AND SEALERS to be accurate. As with all chemicals, KEEP AWAY FROM CHILDREN AND ANIMALS. FOR PROFESSIONAL USE ONLY. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

---