
M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : CLEAR PEN-LUBE
IDENTIFICATION NUMBER: 4550 DATE PRINTED: 08/28/07
PRODUCT USE/CLASS : LUBRICANT

MANUFACTURER/SUPPLIER:
INTERNATIONAL EPOXIES AND SEALERS
30241 COMMERCE DRIVE
SAN ANTONIO, FL 33576
TELEPHONE: (800) 451-7206

EMERGENCY TELEPHONE: INFOTRAC: 1-800-535-5053
OUTSIDE THE U.S. CALL COLLECT: 1-352-323-3500

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	35.0 %
02	N-HEPTANE	142-82-5	20.0 %
03	OLEFIN POLYMER	PROPRIETARY	15.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	1000 PPM	N.E.	800 PPM	N.E.	N.E.	YES
02	400 PPM	500 PPM	400 PPM	500 PPM	N.E.	YES
03	5 MG/M3	10 MG/M3	5 MG/M3	N.E.	N.E.	YES

(See Section 16 for abbreviation legend)

(Continued on Page 2)

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. If a Corrosive product, may cause severe and permanent damage to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Overexposure may cause lung damage. Overexposure may cause kidney damage. May cause liver disorder (e.g., edema, proteinuria) and damage.

PRIMARY ROUTE(S) OF ENTRY: INHALATION SKIN ABSORPTION SKIN CONTACT EYE CONTACT INGESTION

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Get medical attention immediately. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

(Continued on Page 3)

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: -156 F
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 1.2 %
UPPER EXPLOSIVE LIMIT: 9.5 %

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: WATER FOG DRY CHEMICAL CO2 FOAM ALCOHOL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep from freezing.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed

(Continued on Page 4)

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: -43 - 209 F	VAPOR DENSITY	: Is heavier than air
ODOR	: SOLVENT	ODOR THRESHOLD	: ND
APPEARANCE	: CLEAR	EVAPORATION RATE:	Is faster than Butyl Acetate
SOLUBILITY IN H2O	: NEGLIGIBLE	SPECIFIC GRAVITY:	0.6947
FREEZE POINT	: 32	pH @ 0.0 %	: NA
VAPOR PRESSURE	: 80-90	VISCOSITY	: NA
PHYSICAL STATE	: LIQUID		
COEFFICIENT OF WATER/OIL DISTRIBUTION: NEGLIGIBLE			

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES.

INCOMPATIBILITY: STRONG ACIDS, ALKALIS, OXIDIZERS, AND AMINES.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, OXIDES OF NITROGEN, AND MAY PRODUCE FORMS OF CHLORIDE, CHLORINE, AND PHOSGENE.

(Continued on Page 5)

 SECTION 10 - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

 SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT LD50: 7100 mg/kg

PRODUCT LC50: 103000 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

CHEMICAL NAME	LD50	LC50
PROPANE/ISOBUTANE/N-BUTANE	NE	658000 MG/M3/4HRAT
HYDROTREATED, SEVERE, LT. NAPHTHENIC DI	NE	NE
N-HEPTANE	>7100 MG/KG/RAT	103000 MG/M3/4H/RA
OLEFIN POLYMER	ND	ND
PETROLATUM	>50000 MG/KG/MOUSE	NE
LUBE OIL ADDITIVE	NE	NE
MINERAL OIL HYDROTREATED (SEVERE)	ND	ND
ALUMINUM ISOPROPOXIDE	11300 MG/KG/RAT	NE
POLYTETRAFLUOROETHYLENE	NE	NE
PETROLEUM LUBRICATING GREASE	NE	NE
TETRAFLUOROETHYLENE	N.E.	40000 PPM/RAT

 SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

 SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

 SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL - CONSUMER COMMODITY

DOT TECHNICAL NAME: ORM-D

DOT HAZARD CLASS: 2.1

HAZARD SUBCLASS: NA

(Continued on Page 6)

SECTION 14 - TRANSPORTATION INFORMATION

DOT UN/NA NUMBER: UN1950 PACKING GROUP: NA RESP. GUIDE PAGE: 126

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
N-HEPTANE 142-82-5

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME ----- CAS NUMBER
HYDROTREATED, SEVERE, LT. NAPHTHENIC DIST. 64742-52-5
PETROLATUM 8009-03-8

SECTION 15 - REGULATORY INFORMATION

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
HYDROTREATED, SEVERE, LT. NAPHTHENIC DIST.	64742-52-5
PETROLATUM	8009-03-8

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
TETRAFLUOROETHYLENE	116-14-3

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 4 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 01/20/05

REASON FOR REVISION:

NEW FORMAT

VOLATILE ORGANIC COMPOUNDS (VOCS): 2.93 lbs/gal, 351 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.
