



MATERIAL SAFETY DATA SHEET

SECTION 1:	<u>PRODUCT AND COMPANY IDENTIFICATION</u>																
Product Identity: Chemical Name, Family	8801 Inter-Skim Polyester Putty Unsaturated Polyester Resin based putty International Epoxies & Sealers																
Company Identity:	30241 Commerce Drive San Antonio, FL 33576 INFOTRAC: 800-535-5053, Outside the U.S.A, Call Collect: 1-352-323-3500																
	Date 09/28/09																
SECTION 2:	<u>COMPOSITION</u>																
Components:	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>CAS NO.</u> /</th> <th style="text-align: left;"><u>PERCENT</u> /</th> <th style="text-align: left;"><u>OSHA PEL</u> /</th> <th style="text-align: left;"><u>ACGIH TLV</u></th> </tr> </thead> <tbody> <tr> <td>Unsaturated Polyester</td> <td>Proprietary > 35 %</td> <td>N/E</td> <td>N/E</td> </tr> <tr> <td>Styrene Monomer</td> <td>100-42-5 > 15 %</td> <td>50 ppm TWA</td> <td>50 ppm</td> </tr> <tr> <td>Non Hazardous Fillers</td> <td>< 50 %</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>	<u>CAS NO.</u> /	<u>PERCENT</u> /	<u>OSHA PEL</u> /	<u>ACGIH TLV</u>	Unsaturated Polyester	Proprietary > 35 %	N/E	N/E	Styrene Monomer	100-42-5 > 15 %	50 ppm TWA	50 ppm	Non Hazardous Fillers	< 50 %	N/A	N/A
<u>CAS NO.</u> /	<u>PERCENT</u> /	<u>OSHA PEL</u> /	<u>ACGIH TLV</u>														
Unsaturated Polyester	Proprietary > 35 %	N/E	N/E														
Styrene Monomer	100-42-5 > 15 %	50 ppm TWA	50 ppm														
Non Hazardous Fillers	< 50 %	N/A	N/A														
SECTION 3:	<u>HAZARD IDENTIFICATION</u>																
Emergency Overview:	Flammable paste with strong fumes																
Eye Exposure	Avoid Eye contact will be irritating and may cause permanent damage																
Skin Exposure	Avoid excessive skin exposure																
Inhalation	Avoid inhalation of strong fumes especially upon curing																
Ingestion	Do not ingest																
SECTION 4:	<u>FIRST AID MEASURES</u>																
Eyes:	Wash with plenty of water seek medical treatment for prolonged irritation																
Skin:	Wash often with soap and water																
Inhalation:	Move to fresh air Oxygen may be given by trained medical personal																
Ingestion	Seek immediate medical attention do not aspirate material into the lungs																
SECTION 5:	<u>FIRE FIGHTING MEASURES</u>																
Extinguishing Media	Water Foam CO2 or Dry Chemicals																
Flammable Limits:	LEL 1.1 UEL 6.1 Auto ignition Temperature N/E																
Special Procedures:	Full Bunker gear with Self Contained air necessary in enclosed spaces																
Unusual Fire Hazards:	Fumes are heavier than air and may move along the ground empty drums should be kept cool to avoid fume explosions																
NFPA / HMIS code	HMIS: Health 2 Flammability 3 Reactivity 2																
SECTION 6:	<u>ACCIDENTAL RELEASE</u>																
Spill Procedures	Take up as much material as possible in absorbent materials and return to original container, Dispose of remaining materials in accordance with all Federal, State, and local laws																

<u>SECTION 7:</u>	<u>HANDLING AND STORAGE</u>		
Storage	Cool temperatures below 77 F are preferable to maintain shelf life		
<u>SECTION 8:</u>	<u>EXPOSURE CONTROLS</u>		
Exposure	Protection for eye, skin, and inhalation is recommended to avoid exceeding the exposure limits for these products.		
Physical State & Color	White flow able paste	Specific Gravity	1.08
Boiling Point	293 F (144 C)	Melting Point	N/A
Vapor Pressure	4.3 mm Hg @ 38 F	Vapor Density	3.6
Evaporation Rate	3.1 (ButAc 1)	Ph and Odor	Strong Aromatic
Solubility in Water	Slight	TBD	
Other Information	VOC content < 20 %		
<u>SECTION 10</u>	<u>STABILITY AND REACTIVITY</u>		
Stability	Stable at all normal environmental Temperatures		
Incompatible Materials	Strong Acids, Bases, Reactive metals, and Oxidizers		
<u>SECTION 11</u>	<u>TOXICOLOGICAL INFORMATION</u>		
Toxicological	No Carcinogenic properties according to the ACGIH		
<u>SECTION 13</u>	<u>DISPOSAL INFORMATION</u>		
Disposal	Cured material may be disposed of as plastic solid waste, Uncured material must be disposed of in accordance with all Federal State and local laws		
<u>SECTION 14</u>	<u>TRANSPORTATION INFORMATION</u>		
DOT Shipping Name	Resin Solution		
UN, Hazard Class, PG	UN 1866, Class 3 , PG III		
Hazard	Flammable Liquid		
Special Information			
<u>SECTION 15</u>	<u>REGULATORY INFORMATION</u>		
Regulatory	Contains no California Prop 65 carcinogens		
<u>SECTION 16</u>	<u>OTHER INFORMATION</u>		
Other Info.	None		

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.