

Safety Data Sheet

Issue Date: 01-Jun-2004

Revision Date: 28-Mar-2014

Version 1

1. IDENTIFICATION

Product Identifier

Product Name 8410 Inter-Mix 30 Control Flow Seam Sealer Resin

Other means of identification

SDS # IES-FO8410R

Recommended use of the chemical and restrictions on use

Recommended Use Seam Sealer.

Details of the supplier of the safety data sheet

Supplier Address

International Epoxies & Sealers
30241 Commerce Drive
San Antonio, FL 33576

Emergency Telephone Number

Company Phone Number 1-800-451-7206
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Black liquid

Physical State Liquid

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2

Signal Word

Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Get medical attention
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash it before reuse
 If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

30-40% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Polymer of epichlorohydrin and bisphenol A	25085-99-8	60-70
Resin Blend	PROPRIETARY	20-30
Talc	14807-96-6	1-10
(3-Glycidyoxypropyl)trimethoxysilane	2530-83-8	1-3
Silica, fumed	112945-52-5	1-3
Carbon Black	1333-86-4	0-1
Quartz	14808-60-7	0-1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Seek medical attention.

Most important symptoms and effects

Symptoms	Eye, skin, and/or respiratory irritation. Exposed individuals may experience eye tearing, redness and discomfort. Will cause gastrointestinal tract irritation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO₂, dry chemical, foam and water fog.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
Environmental Precautions	Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so. Contain with inert material.
Methods for Clean-Up	Soak up with inert absorbent material. Place in appropriate containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Keep out of the reach of children. Use personal protection recommended in Section 8. Wash face, hands, and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep locked up and out of reach of children.

Incompatible Materials Acids, Amines, Mercaptans, Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Silica, fumed 112945-52-5	-	TWA: 20 Million particles per cubic feet	-
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	(vacated) TWA: 0.1 mg/m ³ respirable dust : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Goggles.

Skin and Body Protection Solvent resistant gloves. Wear suitable protective clothing.

Respiratory Protection Wear an appropriate NIOSH/MSHA approved respirator if ventilation is inadequate.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Not determined
Appearance	Black liquid	Odor Threshold	Not determined
Color	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	Not determined	
Flash Point	> 93.33 °C / > 200 °F	
Evaporation Rate	Not determined	

Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Material V.O.C.	Negligible	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Specific Gravity	1.23	(1=Water)
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Heat, flames and sparks. Keep out of reach of children.

Incompatible Materials

Acids, Amines, Mercaptans, Strong oxidizing agents.

Hazardous Decomposition Products

HES, AMINES, CO, CO2, H2S, SO2, NO2.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

- Eye Contact** Causes serious eye irritation.
- Skin Contact** Causes skin irritation. May cause an allergic skin reaction.
- Inhalation** May cause irritation if inhaled.
- Ingestion** May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Polymer of epichlorohydrin and bisphenol A 25085-99-8	>2000 mg/kg (rat)	>2000 mg/kg (rabbit)	-

(3-Glycidyloxypropyl)trimethoxysilane 2530-83-8	= 22600 µL/kg (Rat)	= 3970 µL/kg (Rabbit)	-
Silica, fumed 112945-52-5	= 3160 mg/kg (Rat)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Quartz 14808-60-7	= 500 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity Suspected of causing cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		
Silica, fumed 112945-52-5		Group 3		
Carbon Black 1333-86-4	A3	Group 2B		X
Quartz 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)
 A2 - Suspected Human Carcinogen
 A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
 Group 1 - Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 IARC components are "not classifiable as human carcinogens"
NTP (National Toxicology Program)
 Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Numerical measures of toxicity

Not determined

Unknown Acute Toxicity 30-40% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		
Carbon Black 1333-86-4				5600: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

<u>Note</u>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
<u>DOT</u>	Not regulated
<u>IATA</u>	Not regulated
<u>IMDG</u> Marine Pollutant	This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION**International Inventories**

Not determined

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances***US Federal Regulations****SARA 313**

Not determined

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Carbon Black - 1333-86-4	Carcinogen
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Talc 14807-96-6	X	X	X
Carbon Black 1333-86-4	X	X	X
Quartz 14808-60-7	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
HMIS	Health Hazards 2	Flammability 1	Physical Hazards 0	Personal Protection Not determined

Issue Date: 01-Jun-2004
 Revision Date: 28-Mar-2014
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet