

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

1 Identification

- **Product identifier**
- **Trade name:** INTER-WAX
- **Article number:** 1695
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Anticorrosion additive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
International Epoxies & Sealers
30241 Commerce Drive
San Antonio, FL 33576
Tel: 1 (800) 451-7206
Email: mail@internationalepoxies.com
- **Information department:** Product safety department.
- **Emergency telephone number:** Tel: 1 (800) 535-5053 INFOTRAC

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Irritant

May cause sensitization by skin contact.



Dangerous for the environment

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 1)

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms** GHS02, GHS07, GHS09

- **Signal word** Warning

- **Hazard-determining components of labeling:**

Calcium Sulfonate

- **Hazard statements**

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Hazard description:**

- **Canadian Hazard Symbols**

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects



- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 3

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

*

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures

· **Description:** Mixture of the substances listed below with additions.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 2)

· Dangerous components:		
CAS: 64742-82-1 EC number: 919-446-0	Naphtha (petroleum), hydrodesulfurized heavy	25-<50%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy	5-<10%
CAS: 61789-86-4	Calcium Sulfonate	5-<10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

*

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** Mount respiratory protective device.

· **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

USA

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 3)

7 Handling and storage

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm

- **Penetration time of glove material**

> 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 4)

· **Body protection:** Use protective suit.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Fluid
Color:	Beige
Odor:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	135 °C

· **Flash point:** 36 °C (DIN 53213)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** > 200 °C· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

Lower:	0.6 Vol %
Upper:	7.0 Vol %

· **Vapor pressure at 20 °C:** 27 hPa· **Vapour pressure at 50 °C:** 15 hPa· **Density at 20 °C:** 0.85 g/cm³ (DIN 51757)· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not determined.
Kinematic at 20 °C:	30 s (DIN 53211/4)

· **Solvent content:**

Organic solvents:	52.8 %
VOC content:	52.8 %

· **Solids content:** 47.2 % (DIN 53216)· **Other information** No further relevant information available.· **VOC (EU):** 52.79 %· **VOC (EU):** 448.7 g/l· **VOC (US):** 448.7 g/l / 3.74 lb/gl

USA

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 5)

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

* 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	8.913 mg/kg (RAT)
Dermal	LD50	5.514 mg/kg
Inhalative	LC50/4 h	30.2 mg/l (RAT)

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	3400 mg/kg (RABBIT)
Inhalative	LC50/4 h	13.1 mg/l (RAT)

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5000 mg/kg (RAT)
Dermal	LD50	>3000 mg/kg (RAT)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

· **Aquatic toxicity:**

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

EC50/48 h	10-22 mg/l (DAPHNIA MAGNA)
EC50/72 h	4.6-10 mg/l (ALGAE)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 6)




EC50/96 h 10-30 mg/L (Fish)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	UN1139
<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG · IATA 	Coating solution 1139 Coating solution, ENVIRONMENTALLY HAZARDOUS, special provision 640E COATING SOLUTION (TURPENTINE SUBSTITUTE), MARINE POLLUTANT COATING SOLUTION
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> · ADR, IMDG 	<div style="text-align: center;">   </div>
<ul style="list-style-type: none"> · Class 	3 Flammable liquids

(Contd. on page 8)

USA

Safety Data Sheet


acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 7)

· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrodesulfurized heavy
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Transport classification ADR/IMGD is based on packaging >30ltr(IMDG), <450ltr(ADR). For other packaging untis different classification can apply. See ADR 2.2.3.1.3/ 2.2.3.1.4 und IMDG 2.3.2.3 / 2.3.2.5
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1139, Coating solution, special provision 640E, 3, III, ENVIRONMENTALLY HAZARDOUS

*

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 8)

- **Proposition 65**

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:
--

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
--

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- **Carcinogenity categories**

· EPA (Environmental Protection Agency)
--

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms** GHS02, GHS07, GHS09

- **Signal word** Warning

- **Hazard-determining components of labeling:**

Calcium Sulfonate

- **Hazard statements**

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department.

- **Contact:** mail@internationalepoxies.com

- **Date of preparation / last revision** 09/25/2014 / 6

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Reviewed on 06/19/2014

Trade name: 1695 Inter-Wax

(Contd. of page 9)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· *** Data compared to the previous version altered.**

USA