

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

1 Identification of the substance and manufacturer

Trade name: GLOSS BLACK ENAMEL
Product code: 4193
Manufacturer/Supplier: International Epoxies and Sealers
 30241 Commerce Drive
 San Antonio, FL 33576
 phone: 1-800-451-7206
Emergency telephone number: INFOTRAC 1-800-535-5053, 1-352-323-3500 *if located outside the U.S.*

2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	21.12%
74-98-6	propane	18.91%
108-88-3	Toluene	15.92%
106-97-8	n-butane	11.11%
64742-89-8	VM&P Naphtha	8.25%
64742-47-8	Mineral Spirits	2.52%
67-63-0	isopropyl alcohol	2.47%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazard(s) identification

Hazard Information for people and the environment:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
 Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
 Has narcotizing effect.

Risk phrases:

Extremely flammable.
 Irritating to eyes.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child

Safety phrases:

Keep locked up and out of the reach of children.
 Keep away from sources of ignition - No smoking.
 Do not breathe gas/fumes/vapour/spray.
 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
 Wear suitable protective clothing and gloves.
 If swallowed, seek medical advice immediately and show this container or label.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4):

Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (0 - 4):

Health= 1
 Fire= 4
 Physical Hazard= 3

4 First-aid measures

After inhalation: If breathing is difficult, administer oxygen.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Do not induce vomiting; immediately call for medical help.
 Rinse out mouth and then drink plenty of water.

5 Fire-fighting measures

Extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.
 CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
 Can form explosive gas-air mixtures.
Special hazards:
Protective equipment for firefighters: A respiratory protective device may be necessary.
Additional information Cool endangered receptacles with water spray.

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

Trade name: GLOSS BLACK ENAMEL

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Inform appropriate authorities in case of seepage into water course or sewage system.
Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.
Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling Fire/explosion protection:

No special precautions are necessary if used correctly.
Do not smoke. Protect from electrostatic charges.
Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm
REL Long-term value: 590 mg/m³, 250 ppm
TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm
BEI

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm
REL Long-term value: 1800 mg/m³, 1000 ppm
TLV refer to Appendix F: minimal oxygen content

108-88-3 Toluene

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift
REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
TLV Long-term value: 75 mg/m³, 20 ppm
BEI

106-97-8 n-butane

REL Long-term value: 1900 mg/m³, 800 ppm
TLV Short-term value: 2370 mg/m³, 1000 ppm

67-63-0 isopropyl alcohol

PEL Long-term value: 980 mg/m³, 400 ppm
REL Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm
TLV Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm
BEI

Ingredients with biological limit values:

67-64-1 Acetone

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

(Contd. on page 3)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

Trade name: GLOSS BLACK ENAMEL

(Contd. of page 2)

108-88-3 Toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

67-63-0 isopropyl alcohol

BEI 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

pH-value: Not determined.

Boiling point: -44 °C (-47 °F)

Flash point: -19 °C (-2 °F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor Pressure: 40 PSI, 2750 hPa

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

VOC content: 544.3 g/l / 4.54 lb/gl

VOC content (less exempt solvents): 60.0 %

Solids content: 18.9 %

Other information No further relevant information available.

10 Stability and reactivity

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information: Harmful

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

108-88-3	Toluene	3
67-63-0	isopropyl alcohol	3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

Trade name: GLOSS BLACK ENAMEL**Other information:**

(Contd. of page 3)

Product does not contain CFC's.
This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	Consumer Commodity Consumer Commodity ORM-D
Class	2.1
Marine pollutant:	No
EMS Number:	F-D,S-U
Packaging Group:	--

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
67-63-0	isopropyl alcohol

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4	Carbon black
100-41-4	ethyl benzene

California Proposition 65 chemicals know to cause developmental toxicity:

108-88-3 Toluene

EPA:

67-64-1	Acetone	I
108-88-3	Toluene	II

IARC: Group 2A: The ingredient is probably carcinogenic to humans.
Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

ACGIH: Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
108-88-3	Toluene	A4
67-63-0	isopropyl alcohol	A4

NIOSH:

1333-86-4	Carbon black
-----------	--------------

16 Other information

This product was manufactured in the U.S.A.
The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health