

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/28/2014

Revised On 01/28/2014

## 1 Identification of the substance and manufacturer

**Trade name:** CLEAR GLOSS TRIM PAINT

**Product code:** 4203

**Product category:** Paints and coatings.

**Manufacturer/Supplier:** International Epoxies & Sealers  
P.O. Box 185  
San Antonio, FL 33576  
Phone: 352-588-2400  
www.useies.com.com

**Emergency telephone number:** INFOTRAC 1-800-535-5053, 1-352-323-3500 \*if located outside the U.S.\*

## 2 Hazard(s) identification

**GHS Hazard pictograms**



GHS02 GHS07 GHS08

**Signal word**

Danger

**Hazard statements**

Extremely flammable aerosol.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Do not pierce or burn, even after use.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**Precautionary statements**

## 3 Composition/information on ingredients

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

67-64-1	Acetone	22.43%
74-98-6	propane	15.7%
108-88-3	Toluene	15.01%
110-19-0	isobutyl acetate	13.13%
111-76-2	Glycol Ether EB	10.51%
106-97-8	n-butane	9.22%
1330-20-7	xylene (mix)	1.95%

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Do not induce vomiting; immediately call for medical help.  
Rinse out mouth and then drink plenty of water.

## 5 Fire-fighting measures

**Extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.  
Can form explosive gas-air mixtures.

**Special hazards:**

**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**Additional information** Cool endangered receptacles with water spray.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.

**Environmental precautions:** Do not allow product to reach sewage systems or ground water.

(Contd. on page 2)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/28/2014

Revised On 01/28/2014

**Trade name:** CLEAR GLOSS TRIM PAINT

(Contd. of page 1)

**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
Dispose contaminated material as waste according to section 13.

**7 Handling and storage****Precautions for safe handling  
Fire/explosion protection:**

No special precautions are necessary if used correctly.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

**Storage requirements:**

Observe pressurized container storage regulations. Consult with your local authorities.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m <sup>3</sup> , (500) NIC-200 ppm BEI

**74-98-6 propane**

PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	refer to Appendix F: minimal oxygen content

**108-88-3 Toluene**

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**110-19-0 isobutyl acetate**

PEL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Long-term value: 713 mg/m <sup>3</sup> , 150 ppm

**111-76-2 Glycol Ether EB**

PEL (USA)	Long-term value: 240 mg/m <sup>3</sup> , 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m <sup>3</sup> , 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m <sup>3</sup> , 20 ppm BEI

**106-97-8 n-butane**

REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm

**1330-20-7 xylene (mix)**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

(Contd. on page 3)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/28/2014

Revised On 01/28/2014

Trade name: CLEAR GLOSS TRIM PAINT

(Contd. of page 2)

**108-88-3 Toluene**

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**111-76-2 Glycol Ether EB**

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

**1330-20-7 xylene (mix)**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
Immediately remove all soiled and contaminated clothing.  
Wash hands after use.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties**

<b>Appearance:</b>	Aerosol.
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Boiling point:</b>	-44 °C (-47 °F)
<b>Flash point:</b>	-19 °C (-2 °F)
<b>Flammability (solid, gaseous):</b>	Not applicable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	1.1 Vol %
<b>Upper Explosion Limit:</b>	10.9 Vol %
<b>Specific Gravity:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>Vapour density:</b>	Not determined.
<b>Evaporation rate:</b>	Not applicable.
<b>Partition coefficient (n-octanol/water):</b>	Not determined.
<b>VOC content:</b>	633.7 g/l / 5.29 lb/gl
<b>VOC content (less exempt solvents):</b>	66.0 %
<b>MIR Value:</b>	1.41
<b>Solids content:</b>	11.7 %
<b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

<b>Conditions to avoid:</b>	Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

**11 Toxicological information**

<b>Skin effects:</b>	Irritant to skin and mucous membranes.
<b>Eye effects:</b>	Irritating effect.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/28/2014

Revised On 01/28/2014

Trade name: CLEAR GLOSS TRIM PAINT

(Contd. of page 3)

**Sensitization:** No sensitizing effects known.

**Carcinogenic categories**

**IARC (International Agency for Research on Cancer)**

108-88-3	Toluene	3
111-76-2	Glycol Ether EB	3
1330-20-7	xylene (mix)	3

**NTP (National Toxicology Program)**

None of the ingredients is listed.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**DOT** N/A  
**ADR** UN1950  
**UN proper shipping name:** UN1950  
**DOT** Consumer Commodity ORM-D  
**ADR** Aerosols, flammable  
**Transport hazard class(es):** 1950 Aerosols  
**Class** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Packaging Group:** --  
**UN "Model Regulation":** UN1950, Aerosols, 2.1

## 15 Regulatory information

**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

108-88-3	Toluene
111-76-2	Glycol Ether EB
1330-20-7	xylene (mix)

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

100-41-4	ethyl benzene
----------	---------------

**California Proposition 65 chemicals know to cause developmental toxicity:** 108-88-3 Toluene

**EPA:**

67-64-1	Acetone	I
108-88-3	Toluene	II
110-19-0	isobutyl acetate	D
111-76-2	Glycol Ether EB	NL
1330-20-7	xylene (mix)	I

**ACGIH:**

67-64-1	Acetone	A4
108-88-3	Toluene	A4
110-19-0	isobutyl acetate	A4
111-76-2	Glycol Ether EB	A3
1330-20-7	xylene (mix)	A4

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/28/2014

Revised On 01/28/2014

**Trade name:**CLEAR GLOSS TRIM PAINT

(Contd. of page 4)

**NIOSH:**

The following substances are regulated in the United States with reference to occupational exposure limits:

**16 Other information**

**Contact:** Regulatory Affairs

US4