

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

1 Identification of the substance and manufacturer

Trade name: GREEN ZINC PHOSPHATE PRIMER

Product code: 04530

Manufacturer/Supplier: International Epoxies & Sealers
P.O. Box 185
San Antonio, FL 33576-0185
Phone: 352-588-2400

Emergency telephone number: INFOTRAC 1-800-535-5053, 1-352-323-3500 *if located outside the U.S.*

2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|------------|----------------------------------------|--------|
| 67-64-1 | Acetone | 33.02% |
| 74-98-6 | propane | 15.73% |
| 106-97-8 | n-butane | 9.24% |
| 108-88-3 | Toluene | 8.37% |
| 66402-68-4 | Calcium Strontium Zinc Phosphosilicate | 7.25% |
| 110-19-0 | isobutyl acetate | 4.36% |
| 64-17-5 | ethyl alcohol | 4.3% |
| 1330-20-7 | xylene (mix) | 3.55% |
| 64742-89-8 | VM&P Naphtha | 1.7% |
| 64742-47-8 | Mineral Spirits | 1.42% |

3 Hazard(s) identification

Hazard Information for people and the environment:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
Has narcotizing effect.

Risk phrases:

Extremely flammable.
Irritating to eyes.
Possible risk of harm to the unborn child
Vapours may cause drowsiness and dizziness

Safety phrases:

Keep out of the reach of children.
Keep away from sources of ignition - No smoking.
Do not breathe gas/fumes/vapour/spray.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4):

Health = 1
Fire = 4
Reactivity = 3

HMS-ratings (0 - 4):

Health= 1
Fire= 4
Physical Hazard= 3

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; immediately call for medical help.
Rinse out mouth and then drink plenty of water.

5 Fire-fighting measures

Extinguishing agents: CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

Trade name: GREEN ZINC PHOSPHATE PRIMER

Additional information

Cool endangered receptacles with water spray.

(Contd. of page 1)

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage**Precautions for safe handling
Fire/explosion protection:**

No special precautions are necessary if used correctly.
Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements:

Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**PEL Long-term value: 2400 mg/m³, 1000 ppmREL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm
BEI

74-98-6 propanePEL Long-term value: 1800 mg/m³, 1000 ppmREL Long-term value: 1800 mg/m³, 1000 ppm

TLV refer to Appendix F: minimal oxygen content

106-97-8 n-butaneREL Long-term value: 1900 mg/m³, 800 ppmTLV Short-term value: 2370 mg/m³, 1000 ppm**108-88-3 Toluene**

PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppmREL Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm
BEI

110-19-0 isobutyl acetatePEL Long-term value: 700 mg/m³, 150 ppmREL Long-term value: 700 mg/m³, 150 ppmTLV Long-term value: 713 mg/m³, 150 ppm**64-17-5 ethyl alcohol**PEL Long-term value: 1900 mg/m³, 1000 ppmREL Long-term value: 1900 mg/m³, 1000 ppmTLV Short-term value: 1880 mg/m³, 1000 ppm**1330-20-7 xylene (mix)**PEL Long-term value: 435 mg/m³, 100 ppmREL Short-term value: 655 mg/m³, 150 ppmREL Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

Ingredients with biological limit values:**67-64-1 Acetone**

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

Trade name: GREEN ZINC PHOSPHATE PRIMER

(Contd. of page 2)

108-88-3 Toluene

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

1330-20-7 xylene (mix)

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing.

Wash hands after use.
 Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Odor: Aromatic

pH-value: Not determined.
Boiling point: -110 °C (-166 °F)

Flash point: -19 °C (-2 °F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.
 In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor Pressure: 40 PSI, 2750 hPa

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

VOC content: 574.2 g/l / 4.79 lb/gl

VOC content (less exempt solvents): 50.4 %

MIR Value: 1.17

Solids content: 16.3 %

Other information No further relevant information available.

10 Stability and reactivity

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Skin effects: No irritant effect.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

| | | |
|-----------|---------------|---|
| 108-88-3 | Toluene | 3 |
| 64-17-5 | ethyl alcohol | 1 |
| 1330-20-7 | xylene (mix) | 3 |

NTP (National Toxicology Program)

None of the ingredients is listed.

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/10/2014

Revised On 01/10/2014

Trade name: GREEN ZINC PHOSPHATE PRIMER

(Contd. of page 3)

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT Consumer Commodity ORM-D
 AEROSOLS, flammable
Class 2.1
Marine pollutant: No
EMS Number: F-D,S-U
Packaging Group: --

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

| | |
|-----------|--------------|
| 108-88-3 | Toluene |
| 1330-20-7 | xylene (mix) |

TSCA: All ingredients are listed.**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

| | |
|-----------|------------------------|
| 100-41-4 | ethyl benzene |
| 108-10-1 | methyl isobutyl ketone |
| 1333-86-4 | Carbon black |

California Proposition 65 chemicals know to cause developmental toxicity:

| | |
|----------|----------|
| 108-88-3 | Toluene |
| 67-56-1 | Methanol |

EPA:

| | | |
|-----------|------------------|----|
| 67-64-1 | Acetone | I |
| 108-88-3 | Toluene | II |
| 110-19-0 | isobutyl acetate | D |
| 1330-20-7 | xylene (mix) | I |

ACGIH:

| | | |
|-----------|------------------|----|
| 67-64-1 | Acetone | A4 |
| 108-88-3 | Toluene | A4 |
| 110-19-0 | isobutyl acetate | A4 |
| 64-17-5 | ethyl alcohol | A3 |
| 1330-20-7 | xylene (mix) | A4 |

NIOSH:

| | |
|-----------|--------------|
| 1333-86-4 | Carbon black |
|-----------|--------------|

16 Other information

This product was manufactured in the U.S.A.
 The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health