



Black Mastic Aluminum Sound Deadener Pads

A great black mastic aluminum sound deadener pad for all your vibration and sound dampening needs! OEM approved and very easy to apply. Material doesn't absorb water and doesn't separate under environment influences. Great anti-corrosion and hermetic properties. Can be easily attached on compound surfaces and doesn't demand heating during attaching. Great for Autos, Trucks, Boats, Campers, Buses, Airplanes, Industrial and Agricultural divisions and anywhere else where noise, vibration and sound deadening insulation is needed.

APPEARANCE

Black butyl based core, black aluminum constrain layer, craft paper release liner.

APPLICATIONS

Automotive: Doors, Floors, Trunks, Hoods, Roofs, Firewall
Industrial: Partitions, Bins, Doors, Cabinets, Ducts, Steel Furniture, Computer Equipment, and much more.

BENEFITS

Very Easy To Apply - Self-Adhesive!
Paintable
Reflects and Blocks Heat , Protecting your Interior
Decrease Road, Engine and Exhaust Vibrations, Rattles and Noise
May Be Cut For Customization
Conforms To Irregular Shapes
OEM Approved!

PROPERTIES

Thickness	2.3mm (3/32")
Weight 1 m ² , kg, not less	4
Intended Service Temp. Range	-49°F - 212°F (-45°C - 100°C) <i>(short periods of time to 190°C)</i>
Water Absorption	None
Anti-Corrosion Properties	Yes
Bonding Strength	Not less than 5 N/sm
Durability of connection between the material and the bearing surface, N/cm, at least	5.0

DIRECTIONS

1. Product should be cut to desired size before applying.
2. Remove any dirt, grease, moisture or other contaminates from the application surface before applying.
3. Peel of the release liner.
4. Apply pad to the desired location, pressing firmly into place. A roller may be necessary for larger applications to remove any air pockets.

STORAGE

Product should be stored in a cool, dry location at a temperature between 50°F to 86°F (10°C to 30°C), temperature not to exceed 104°F (40°C) . Do not store in direct sunlight Material should be stored horizontally in its original packaging.

PRODUCT AVAILABLE

1583	Sheet Size: 14.75" x 29.5" 3/32" (2.3mm) thick 18 sq. ft. total per box	6 sheets per box
-------------	---	------------------

These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. International Epoxies & Sealers shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith.