

## MTP-1 MOULDING TAPE PRIMER

MTP-1 Moulding Tape Primer is designed to work in conjunction with IES Conform Tape, Y2K Acrylic HIGHBOND and INTER-MOUNT moulding tapes.

Specifically designed to leave an acrylic polymer film (adhesion promoter) on the surface to achieve maximum adhesion of the attachment tape to the moulding. Mouldings made out of PVC and other certain plastics (see Moulding Tape Application Chart inside of tape package) require use of MTP-1 Moulding Tape Primer to prevent expensive mouldings from falling off.

**CAUTION - May harm paint surfaces! Apply primer and moulding tape prior to painting moulding!**

### DIRECTIONS

1. Remove all old tape from the moulding and the vehicle.
2. Clean surfaces to be bonded with IES Super Clean or IES Specialty Adhesive Remover.
3. Apply MTP-1 Primer to the back surface of the moulding in a uniform coat. Allow to dry.
4. Align the tape then firmly and evenly attach the moulding tape to the moulding.
5. Paint moulding if necessary.
6. Clean the bond area of the vehicle.
7. Align and attach moulding. Press firmly into place.

**NOTE: when using Conform-Tape Premium or HIGH-BOND Moulding Tapes:**

**Use with MTP-1 Moulding Tape Primer for maximum performance!**



### CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

### STORAGE

Should be stored in a cool, dry location at a temperature between 50°F to 86°F (10°C to 30°C).

### PRODUCT AVAILABLE

**70774**      4 oz. dauber top bottle      12/Box

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.

International Epoxies & Sealers | P.O. Box 185 San Antonio, FL 33576 USA | www.useies.com | Toll Free: (800) 451-7206