

# SAFETY DATA SHEET.

Issuing date 28-Apr-2017

Revision Date 25-Apr-2018

Version 2

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product name** 4509 FAST DRYING RUBBERIZED INDERCOAT

**Recommended use of the chemical and restrictions on use**

**Product code** 4509

**Product Type** Extremely Flammable Aerosol  
**Synonyms** None

**Supplier's details**

**Recommended Use** Undercoating.  
**Uses advised against** No information available

**Manufacturer:**  
International Epoxies & Sealers  
P.O. Box 185  
San Antonio, FL 33576  
Phone: 1-800-451-7206

**Emergency telephone number**  
**Chemical Emergency Phone Number** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)  
**Emergency telephone** INTERNATIONAL EPOXIES & SEALERS 1-800-451-7206



**Precautionary Statements - Disposal**

Dispose of contents, container to an approved waste disposal plant.

**Hazards not otherwise classified (HNOC)**

None

**Other information**

0% of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
CALCIUM CARBONATE	1317-65-3	30-40
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
PETROLEUM DISTILLATES	64742-89-8	1-10
TOLUENE	108-88-3	1-10
METHYL ACETATE	79-20-9	1-10
METHANOL	67-56-1	<1
SOLVENT NAPHTHA	64742-94-5	<1
XYLENE	1330-20-7	<1
CARBON BLACK	1333-86-4	<1
SILICA, CRYSTALLINE	14808-60-7	<0.1
ETHYL BENZENE	100-41-4	<0.1
BENZENE	71-43-2	<0.1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures for different exposure routes**

<b>General advice</b>	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
<b>Eye contact</b>	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
<b>Skin contact</b>	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

<b>Main Symptoms</b>	Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
----------------------	---

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Water fog.Dry chemical. Foam.Carbon dioxide (CO2). Cool containers/tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire. Keep away from sources of ignition - No smoking.

### **Specific hazards arising from the chemical**

Keep product and empty container away from heat and sources of ignition. Extremely Flammable / Flammable. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

### **Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers. In the event of fire and/or explosion do not breathe fumes.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.

### **Environmental precautions**

**Environmental precautions** Vapors can accumulate in low areas. Do not allow material to contaminate ground water system. Report spills as required by local and federal regulations. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.

### **Methods and materials for containment and cleaning up**

**Methods for Containment** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods for cleaning up** Soak up with inert absorbent material. Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.

## 7. HANDLING AND STORAGE

### **Precautions for safe handling**

**Advice on safe handling** Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Handle in accordance with good industrial hygiene and safety practice. Do not puncture or incinerate cans. Contents under pressure. Take precautionary measures against static discharges.

### **Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, oxidizing agents.

**Aerosol Level** 1

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m <sup>3</sup>	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	Not Established
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
SILICA, CRYSTALLINE 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	(vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (30)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (250)/( %SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

<p>BENZENE 71-43-2</p>	<p>STEL: 2.5 ppm TWA: 0.5 ppm Skin - potential significant contribution to overall exposure by the cutaneous route</p>	<p>TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028</p>	<p>IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm</p>
----------------------------	--	--	---

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls**

**Engineering Measures** Ventilation systems. Use adequate ventilation to keep the exposure levels below the occupational exposure limits. Showers. Eyewash stations. Showers, eyewash stations, and ventilation systems.

**Individual protection measures, such as personal protective equipment**

- Eye/Face Protection** Tightly fitting safety goggles.
- Skin and body protection** Chemical resistant apron. Protective gloves.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Avoid breathing vapors, mist or gas. Wear personal protective equipment.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and chemical properties**

<b>Physical state</b>	Aerosol	<b>Odor</b>	Solvent
<b>Appearance</b>	Opaque	<b>Odor Threshold</b>	
<b>Color</b>	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
<b>pH</b>	No information available	
<b>Melting/freezing point</b>	No information available	
<b>Boiling point/boiling range</b>		
<b>Flash Point</b>	-104 °C / -155 °F	Based on propellant
<b>Evaporation rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limits in Air</b>		
upper flammability limit		
lower flammability limit		

Vapor pressure		
Vapor density		
Specific Gravity	1.189	
Water solubility	None	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

**Other information**

VOC Content(%) 39.88

## 10. STABILITY AND REACTIVITY

**Reactivity**

Stable under recommended storage conditions

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Heat, flames and sparks. Extremes of temperature and direct sunlight.

**Incompatible Materials**

Strong acids, alkalis, oxidizing agents.

**Hazardous Decomposition Products**

Carbon oxides , Hydrocarbons, Fumes.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Respiratory irritation may occur if excessive exposure to product by inhalation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Skin irritation may occur if person excessively exposes product to the skin.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg ( Rabbit )	-
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
METHYL ACETATE 79-20-9	> 5 g/kg ( Rat )	> 5 g/kg ( Rabbit )	= 16000 ppm ( Rat ) 4 h
METHANOL 67-56-1	= 6200 mg/kg ( Rat )	-	= 22500 ppm ( Rat ) 8 h
SOLVENT NAPHTHA 64742-94-5	> 5000 mg/kg ( Rat )	> 2 mL/kg ( Rabbit )	> 590 mg/m <sup>3</sup> ( Rat ) 4 h

XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg ( Rat )	-	-
SILICA, CRYSTALLINE 14808-60-7	= 500 mg/kg ( Rat )	-	-
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
BENZENE 71-43-2	= 810 mg/kg ( Rat )	> 8200 mg/kg ( Rabbit )	= 44.66 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (listed below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Under normal conditions there is no skin irritation. Excessive exposure of product with skin may cause skin irritation.

**Eye damage/irritation** Irritating to eyes.

**Sensitization** Not a known sensitizer.

**Germ Cell Mutagenicity** Not a germ cell mutagen.

**Carcinogenicity** The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
XYLENE 1330-20-7	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	-
SILICA, CRYSTALLINE 14808-60-7	A2	Group 1	Known	X
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-
BENZENE 71-43-2	A1	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** Product is or contains a chemical which is a known or suspected reproductive hazard.

**Specific target organ systemic toxicity (single exposure)** No known effect based on information supplied.

**Specific target organ systemic toxicity (repeated exposure)** May cause damage to target organs listed below through prolonged and repeated exposure.

**Chronic toxicity** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.

**Target Organ Effects** Eyes, Skin, Liver, Kidney, Lungs, Central Nervous System, Blood, Bone Marrow, and Respiratory System.

**Neurological effects** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 25594 mg/kg

ATEmix (dermal) 21180 mg/kg



ATEmix (inhalation-dust/mist) 128.2 mg/l

## 12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-89-8	4700 mg/L EC50 Pseudokirchneriella subcapitata 72h	-	-	-
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
METHYL ACETATE 79-20-9	120 mg/L EC50 Desmodesmus subspicatus 72h	295 - 348 mg/L LC50 Pimephales promelas 96h flow-through 250 - 350 mg/L LC50 Brachydanio rerio 96h static	-	1026.7 mg/L EC50 Daphnia magna 48h
METHANOL 67-56-1	-	28200 mg/L LC50 Pimephales promelas 96h flow-through 100 mg/L LC50 Pimephales promelas 96h static 19500 - 20700 mg/L LC50 Oncorhynchus mykiss 96h flow-through 18 - 20 mL/L LC50 Oncorhynchus mykiss 96h static 13500 - 17600 mg/L LC50 Lepomis macrochirus 96h flow-through	-	-
SOLVENT NAPHTHA 64742-94-5	-	19 mg/L LC50 Pimephales promelas 96h static 2.34 mg/L LC50 Oncorhynchus mykiss 96h 1740 mg/L LC50 Lepomis macrochirus 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through 41 mg/L LC50 Pimephales promelas 96h	-	0.95 mg/L EC50 Daphnia magna 48h

XYLENE 1330-20-7	-	13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static	-	3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 32 mg/L LC50 Lepomis macrochirus 96h static 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h
BENZENE 71-43-2	29 mg/L EC50 Pseudokirchneriella subcapitata 72h	10.7 - 14.7 mg/L LC50 Pimephales promelas 96h flow-through 5.3 mg/L LC50 Oncorhynchus mykiss 96h flow-through 22.49 mg/L LC50 Lepomis macrochirus 96h static 28.6 mg/L LC50 Poecilia reticulata 96h static 22330 - 41160 µg/L LC50 Pimephales promelas 96h static 70000 - 142000 µg/L LC50 Lepomis macrochirus 96h static	-	8.76 - 15.6 mg/L EC50 Daphnia magna 48h Static 10 mg/L EC50 Daphnia magna 48h

**Persistence and degradability**

.

**Bioaccumulation**

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
TOLUENE 108-88-3	2.7
METHYL ACETATE 79-20-9	0.18
METHANOL 67-56-1	-0.77
SOLVENT NAPHTHA 64742-94-5	2.9 - 6.1
XYLENE 1330-20-7	2.77 - 3.15
ETHYL BENZENE 100-41-4	3.2

BENZENE 71-43-2	2.1
--------------------	-----

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations. Dispose of in accordance with federal, state, and local regulations. Dispose of contents/container in accordance with local regulation.

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD.QTY.

**IMDG** UN1950, AEROSOLS, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
CALCIUM CARBONATE	X	X	X	X	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	Not listed	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	Not listed	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
METHYL ACETATE	X	X	X	X	X	X	X	X
METHANOL	X	X	X	X	X	X	X	X
SOLVENT NAPHTHA	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
CARBON BLACK	X	X	X	X	X	X	X	X
SILICA, CRYSTALLINE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
BENZENE	X	X	X	X	X	X	X	X

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**CHINA** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**U.S. Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	1-10	1.0
METHANOL - 67-56-1	67-56-1	<1	1.0
XYLENE - 1330-20-7	1330-20-7	<1	1.0
ETHYL BENZENE - 100-41-4	100-41-4	<0.1	0.1
BENZENE - 71-43-2	71-43-2	<0.1	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

**Clean Water Act**

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE 71-43-2	10 lb	X	X	X

**CERCLA**

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
METHANOL 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE 71-43-2	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

**U.S. State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Carbon Black (CAS # 1333-86-4), must be airborne, unbound, and of a particle size < 10 micrometers in diameter to be considered a Proposition 65 chemical. For this product, Carbon Black is bound in the product and no inhalation exposure will occur during the handling or use of this product in this application.

This product as supplied, does not contain respirable particles of crystalline silica.(CAS # 14808-60-7) Such bound and non-respirable particles are not considered to be hazardous under Proposition 65.



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Chemical Name	California Prop. 65
TOLUENE - 108-88-3	Developmental/ 1-10%
METHANOL - 67-56-1	Developmental / <1%
CARBON BLACK - 1333-86-4	Cancer / <1%
SILICA, CRYSTALLINE - 14808-60-7	Cancer /<0.1%
ETHYL BENZENE - 100-41-4	Cancer / <0.1%
BENZENE - 71-43-2	Cancer Developmental (Male) /<0.1%

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
CALCIUM CARBONATE 1317-65-3	X	X	X
PETROLEUM DISTILLATES 64742-89-8			X
TOLUENE 108-88-3	X	X	X
METHYL ACETATE 79-20-9	X	X	X
METHANOL 67-56-1	X	X	X
XYLENE 1330-20-7	X	X	X
CARBON BLACK 1333-86-4	X	X	X
SILICA, CRYSTALLINE 14808-60-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE 71-43-2	X	X	X

**EPA Pesticide Registration Number** Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<b><u>HMIS</u></b>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B
<i>Chronic Hazard Star Legend</i>		<i>Chronic Health Star Hazard Repeated or prolonged exposure may cause damage</i>		<i>central nervous system</i>

**Prepared By** International Epoxies & Sealers  
 30241 Commerce Drive  
 San Antonio, FL 33576

**Issuing date** 28-Apr-2017  
**Revision Date** 25-Apr-2018

**Revision Note**  
 (M)SDS sections updated 15

**Disclaimer**  
 The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**