

Dielectric Silicone Grease

IES Dielectric Silicone Grease is a non-curing lubricant made with 100% silicone oil which resists water and most chemicals. It has excellent dielectric properties and prevents water from contacting electrical components and shorting out. Non-corrosive and performs extremely well in high and low temperatures. Ideal for home use or major industry. Syringe applicator for precision applications.



TYPICAL APPLICATIONS

Spark Plugs (Rubber boot of the plug wire)
Battery Terminals
Terminal Splices, Strips and Disconnects
Electrical Connections
Ignition Coil Connectors
Cable Connections
Gaskets of Multi-Pin Connectors (Car and marine engines)
Speedometer Cables
Headlight and Bulb Connectors
Trailer Hitches
Brake Calipers
Rotors
Distributor Caps
O-Rings

BENEFITS

Seals Out Moisture
Prevents Corrosion
Protects Electrical Components
Wide Temperature Range (-40° to 400°F)
Long Life
Resists Washing Away
Resists Water and Most Chemicals
Compatible With Most Rubbers and Plastics
Ideal For Outdoor Applications
Extreme Temperature Stability
Oxidation Resistance
Non-Toxic, Odorless

TYPICAL PROPERTIES

Appearance: Translucent Paste
Penetration Range: 200-300
Bleed Max (%): 1
Evaporation max (%): 2
Specific Gravity: 1.03
Temp. Range: -40°C to 204°C (-40°F to 400°F)

Seals Out Moisture

Prevents Corrosion

Protects Electrical Components

Lubricates Rubber and Plastic

DIRECTIONS

1. Make sure all surfaces or parts are clean and free of greases.
2. Apply a small amount of product to surfaces or parts.
3. Spread evenly to avoid build-up and clumping.

STORAGE

Product should be stored in a cool, dry location in unopened containers at a temperature between 50°F to 85°F (10°C to 30°C) unless otherwise labeled. Protect package from direct sunlight and heat. To prevent contamination of unused material, do not return any material to its original container.

PRODUCT AVAILABLE

1410 .75 fl. oz. Syringe Applicator 4/box



These suggestions and data are based on information we believe to be reliable and accurate, but no guarantee of their accuracy is made. International Epoxies & Sealers shall not be liable for any damage, loss or injury, direct or consequential arising out of the use or the inability to use the product. In every case, we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine whether the product is of satisfactory quality and suitability for their operations, and the user assumes all risk and liability whatsoever, in connection therewith.