

RUBBER ASSEMBLY LUBRICANT

Provides temporary lubrication that makes rubber parts easier to install, remove or position. Reduces friction by 70%.

Use on: Rubber, Most Plastics & Metal

- Silicone Free
- Non-Toxic, Biodegradable
- Dry Time 1 Hour Approximately
- Once Assembled, the Lubricant dries, the parts return to their original condition and will not become slippery again, even in the presence of moisture.

USES

Weather Strips, Door Seals, Hoses, Grommets, Seals, Bushings, Engine Mounts, Insulators, Sleeves, Wiring Harnesses, Brake Lines, Transmission Lines, Tire Mounting, O-rings, Bumpers, Plugs, Boots, Bearings, Air Intake Hoses, and much more!

SPECIFICATIONS

IES-1422 Lubricant	Emulsion
Color	White - Opaque
PH	7.5 to 9.5
Estimated Minimum Dry Time	1 Hour
Viscosity, cps @25 Deg. C	150
Biodegradable	Yes
Reduction of Friction	~70 %

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.



DIRECTIONS

1. Apply a thin layer of lubricant to the mating surfaces of the assembly.
2. IES-1422 may be applied with a brush, spray or by dip.
3. Allow 1-hour dry time. Once dry IES-1422 pretty much vanishes.

NOTE: Avoid extended contact with uncured paint, or copper and its alloys. May craze polycarbonate, polymethyl methacrylate and polyphenylene oxide.

STORAGE/SHELF LIFE

Should be stored in a cool, dry location at a temperature between 36°F to 86°F (2°C to 30°C). Avoid storing in sunlight. Prevent freezing. Keep container closed when not in use.

PRODUCT AVAILABLE

1422 4 oz. flip-top bottle 12/Box

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.

International Epoxies & Sealers | P.O. Box 185 San Antonio, FL 33576 USA | www.useies.com | Toll Free: (800) 451-7206