

#4508

Classic Car Premium Paintable Rubberized Undercoat

A premium quality, rubber based undercoating with outstanding adhesion and abrasion resistance. Exceptionally tough and highly flexible. Use on undercarriage, doors, trunks and fenders. Good texture and is paintable. Seals and protects. Sound Deadens. Prevents rust. Will not chip, crack or peel.

BENEFITS

Seals and protects
Sound deadener
Rust preventative
Superior salt corrosion protection
50 State Compliant

APPLICATIONS

All automotive types
Can be used as a protective coating for metal applications

TECHNICAL DATA

Appearance	Black
Odor	Petroleum
Evaporation Rate	Slower than ether
VOC Content (%)	27.7

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

STORAGE

Should be stored in a clean, dry and well ventilated location between 50°F to 86°F (10°C to 30°C).



FAST DRYING
PAINTABLE
HIGH SOLIDS
SEALS AND PROTECTS-
PREVENTS RUST

DIRECTIONS

1. Shake well before using. Ensure that agitator ball moves freely. Reshake intermittently during use.
2. Surface to be sprayed should be dry and free of all loose contaminants.
3. Hold can 12-14 inches from surface and apply a uniform coating by moving from side to side and overlapping the strokes.
4. Care should be taken to protect surrounding areas from possible overspray.
5. Paintable when dry.

PRODUCT AVAILABLE

4508	24 oz. Aerosol Can Net Weight 19.4 oz.	12 per case
-------------	---	-------------

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.