

SPECIALTY ADHESIVE REMOVER

An extra strength, fast acting remover used for removing epoxies, urethanes and silicones. Will not leave an oily film or residue. Non-staining. Fast drying. Contains no Chlorinated Solvents or CFC's. 50 State Compliant!

APPLICATIONS

Removing stubborn adhesives
Removing epoxy urethanes & silicone

BENEFITS

Leaves No Film or Residue
Cleans a wide variety of contaminates
Dries Fast
Non-Staining
No Chlorinated Solvents or CFC's
Body Shop Safe (See Note)
50 State Compliant!

TECHNICAL DATA

| | |
|------------------|-------------|
| Color | Light Amber |
| Odor | Solvent |
| Specific Gravity | .780 - .838 |
| Water Solubility | Negligible |

STORAGE

Product should be stored in a cool, dry location in unopened containers at a temperature between 50°F to 85°F (10°C to 30°C) unless otherwise labeled. Protect package from direct sunlight and heat. Do not handle or store near open flame or other sources.



DIRECTIONS

1. Dampen cloth with IES Specialty Adhesive Remover.
2. CAUTION: Test on painted surfaces to determine if it affects paint.
3. Lightly wipe areas to be cleaned.

NOTE: Always test product on painted surface and plastic prior to using.

CAUTION

For professional use only. Before using this or any IES product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

PRODUCT AVAILABLE

| | | |
|------|--------------------|-------------|
| 1780 | 32 fl. oz. Can | 12 per case |
| 4780 | 24 oz. Aerosol Can | 12 per case |

Net Weight 17 oz.

NOTICE TO PURCHASER: The following warranty is in lieu of all other expressed or implied warranties, specifically all goods are manufactured of first class materials and by competent professionals. We have no control over the use and application of our products. Our liability shall not exceed the purchase price.